

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 December 2005 (01.12.2005)

PCT

(10) International Publication Number
WO 2005/115060 A1

(51) International Patent Classification⁷: **H05B 33/12**,
33/14, 33/22

(21) International Application Number:
PCT/JP2005/009313

(22) International Filing Date: 17 May 2005 (17.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-152491 21 May 2004 (21.05.2004) JP

(71) Applicant (for all designated States except US): SEMI-
CONDUCTOR ENERGY LABORATORY CO., LTD.
[JP/JP]; 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP).

(71) Applicant and

(72) Inventor (for all designated States except US): KUMAKI,
Daisuke [JP/JP]; FINE-LIFE OHKURA #202, 19-17, 5
cho-me, Ohkura, Setagaya-ku, Tokyo, 1570074 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): IKEDA, Hisao
[JP/JP]; c/o SEMICONDUCTOR ENERGY LABORA-
TORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa,
2430036 (JP). ABE, Hiroko [JP/JP]; c/o SEMICON-
DUCTOR ENERGY LABORATORY CO., LTD., 398,

Hase, Atsugi-shi, Kanagawa, 2430036 (JP). SEO, Satoshi
[JP/JP]; c/o SEMICONDUCTOR ENERGY LABORA-
TORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa,
2430036 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ,
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,
SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: LIGHT EMITTING ELEMENT AND LIGHT EMITTING DEVICE



(57) Abstract: A light emitting element of the invention includes n pieces of light emitting layers (n is a natural number) between first and second electrodes. A first layer and a second layer are provided between the mth light emitting layer (m is a natural number of 1 ≤ m ≤ n) and the m + 1th light emitting layer. The first and second layers are contacted to each other. The first layer contains a substance that transports holes easily and a substance with an electron accepting property. The second layer contains a substance that transports electrons easily and a substance with an electron donating property. Molybdenum oxide is used as the substance with the electron accepting property.